



**STANDARD AL-22**

High Quality general purpose mineral oil base with water absorbing additives. Provides all around lubrication and rust prevention. Best used during normal operating temperatures in well ventilated areas.

*Available in Gallons, Quarts and Pints*



**FROSTGUARD SYN-AL**

Our best oil. 100% Synthetic, Non Petroleum oil that provides superior air tool lubrication and prevents freezing under the most extreme conditions (-70<sup>0</sup> to 200<sup>0</sup> F). Created to lubricate without the environmental risks of inhalation hazards found in petroleum.

*Available in Gallons, Quarts and Pints*



**ROCK DRILL AIR-OIL 8099020103**

Semi-synthetic pneumatic rock drill lubricant. Thick viscosity oil for Rock Drill lower end. For temperatures from -25°C – -108°C. Readily biodegradable. Low sensitivity against temperature changes.

*Available in Gallons only*



**Impact Wrench Lubricant**

A superior synthetic moly-based extreme pressure lubricant for use in all types of grease-lubricated impact wrench mechanisms, anvil bushings and high speed air motor bearings.

*Cartridge (14.5 oz): CA131898 Pail (7-1/2lbs): C131689*

<b>Index No</b>	<b>Part No</b>	<b>Description</b>
1	AL-22-GAL	AIR TOOL OIL (gallon) (ISO 10)
2	AL-22-QT	AIR TOOL OIL (quart) (ISO 10)
3	AL-22-PT	AIR TOOL OIL (pint) (ISO 10)
4	SYN-AL-1GAL	FROSTGUARD (gallon)
5	SYN-AL-QUART	FROSTGUARD (quart)
6	SYN-AL-PINT	FROSTGUARD (pint)
7	8099020103	AIR-OIL 1GAL ROCK DRILL
9	CA131898	HAMMER/GEAR GREASE 14.5 OZ CARTRIDGE
10	C131689	HAMMER/GEAR GREASE 7-1/2lbs